



RAMPA®-Muffen Typ C  
dünnwandig mit Schlitz

RAMPA®-inserts type C  
slotted and thin-walled

## C

Art.	D	L	d	Vorbohrung Pilot hole	Stahl verzinkt Steel zinc plated	Messing blank Brass plain
005 508	8	8	M 5	6,5 – 7,0	•	
005 510	8	10	M 5	6,5 – 7,0	•	
005 512	8	12	M 5	6,5 – 7,0	•	
005 515	8	15	M 5	6,5 – 7,0	•	
005 632	9,3	12	M 6	7,8 – 8,3	•	
005 637	9,3	17	M 6	7,8 – 8,3	•	
005 640	9,3	20	M 6	7,8 – 8,3	•	
005 610	10	10	M 6	8,0 – 8,5	•	•
005 612	10	12	M 6	8,0 – 8,5	•	
005 614	10	14	M 6	8,0 – 8,5	•	•
005 615	10	15	M 6	8,0 – 8,5	•	
005 617	10	17	M 6	8,0 – 8,5	•	
005 618	10	18	M 6	8,0 – 8,5	•	
005 620	10	20	M 6	8,0 – 8,5	•	
005 810	12	10	M 8	10,0 – 10,5	•	
005 812	12	12	M 8	10,0 – 10,5	•	
005 910	14	10	M 10x1	12,0 – 12,5	•	
005 155	14	15	M 10	12,0 – 12,5	•	
005 158	14	18	M 10	12,0 – 12,5	•	
005 160	14	20	M 10	12,0 – 12,5	•	
005 163	14	23	M 10	12,0 – 12,5	•	
005 116	16	16	M 10	12,5 – 13,5	•	
005 118	16	18	M 10	12,5 – 13,5	•	
005 123	16	23	M 10	12,5 – 13,5	•	
005 136	16	36	M 10	12,5 – 13,5	•	



Bitte ergänzen / Please complete

001

01